

Bund Paint



Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds

COATINGS

- ▲ **Flexible Chemical and Waterproof Paint**
- ▲ **Outstanding Chemical Resistance**
- ▲ **Internal and External Use**
- ▲ **Easy to Mix - No Waste - 50/50 Mixing Ratio**



EPOXY PRODUCTS BUND PAINT is a tough, flexible, highly chemical resistant and waterproof epoxy resin coating for the complete protection of metal and concrete tanks and structures.

EPOXY PRODUCTS BUND PAINT can be applied onto dry or damp surfaces both internally and externally.

EPOXY PRODUCTS BUND PAINT is a thick, flexible, brush applied coating that will bond and adhere to brick, concrete, blockwork and steel.

EPOXY PRODUCTS BUND PAINT is ideal for the complete waterproofing of gutter linings and bund areas holding hazardous chemicals in storage. Resistant to spillages from water, oil, petrol, diesel and a wide range of industrial chemicals.

Pack: 4 kg twin packs - Twin Pack mixed 50 /50 by volume

Available in both Black and Grey

Epoxy Products Limited
Unit 7 Haviland Road
Ferndown Ind. Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983
Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

Pitch Epoxy Coating



Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds

COATINGS

Epoxy Products Limited
Unit 7 Haviland Road
Ferndown Ind. Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983

Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

DESCRIPTION

EPOXY PRODUCTS BUND PAINT is a twin pack epoxy resin coating. When fully cured, the material provides a flexible, abrasion, chemical resistant and waterproof coating of outstanding durability for both interior and exterior applications.

USES

For bund areas to retain spillages from oil, petrol, diesel and a wide range of chemicals. For the complete waterproofing of gutter linings and as a protective coating for steel.

PREPARATION

Surfaces must be clean, sound and free from surface contamination. Surfaces can be damp, although for more permanent installations we recommend that the surface is as dry as possible. Large cracks must be repaired prior to applying BUND PAINT. Excellent repairs can be carried out using EPOXY PRODUCTS PATCHING MORTAR. Joints or cracks can be bridged by BUND PAINT using a 75mm wide Fibreglass Reinforcing Tape. BUND PAINT can be applied onto painted surfaces but all loose paint must be removed. Remove all loose metal rust by wire brushing. Severe heavily corroded metal should be treated with a suitable rust converter prior to painting with BUND PAINT.

MIXING

Empty the entire contents of Pack "B" (Hardener) into Pack "A" (Resin) and stir thoroughly using an electric drill and mixing paddle on a slow speed. Once mixed use all within 45 minutes at 20°C. The higher the ambient room temperature the shorter the useable life.

APPLICATION

Apply by brush, working well into the substrate. Apply evenly and as generously as required to provide a continuous film of resin. One coat is normally adequate to produce a watertight seal but a second coat maybe necessary particularly on porous or open blockwork to achieve a watertight seal.

FIBREGLASS REINFORCING TAPE

Prepare the surface as required. Mix and apply the BUND PAINT 100mm either side of the joints and cracks. While the surface remains wet and tacky, place the Fibreglass Reinforcing Tape onto the BUND PAINT and press to ensure the tape is well embedded. Tape can be pushed onto wet BUND PAINT and placed along right angles and corners of the structure. Alternatively, all joints, cracks, corners and angles can be treated first with the Fibreglass Reinforcing Tape and BUND PAINT and allowed to harden. A full top coat of BUND PAINT can then applied over the entire area as one continuous coating.

HEALTH AND SAFETY

Read the Health and Safety Data Sheet prior to handling this product.

PRODUCT DATA

APPEARANCE

Thick viscous liquid in Black or Grey

COVERAGE

Approximately 7m² per 4kgs depending upon substrate surface texture and porosity.

POT LIFE

When fully mixed 45 minutes @ 20°C. Extended pot life at lower temperatures, reduced at high temperatures.

HARDENING/CURE TIME

Tack free in 24 hours @ 20°C. Full cure in 7 days. Do not use at temperatures below 5°C.

CHEMICAL RESISTANCE

Resistant to a wide range of acids, alkalis, solvents and chemicals found within industry. Limited or no resistance to Acetic Acid, Lactic Acid, Xylene, Benzyl Alcohol, Skydrol and Paint Strippers. If in doubt please contact us for further information.

TOOL CLEANING

Clean all tools with EPOXY PRODUCTS CLEANING SOLVENT.

AVAILABILITY

Twin pack product. Combined volume of Resin and Hardener making 4 kgs