

Cleaning Solvent



Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds

CLEANERS

- ▲ **Excellent Tool Cleaner**
- ▲ **Rapid Removal of wet Epoxy Resins**
- ▲ **Removes Oil from Painted Floors**
- ▲ **Removes Oil Patches from Concrete**



EPOXY PRODUCTS CLEANING SOLVENT is a powerful blend of solvents for the rapid cleansing of all hand tools and mixing equipment having used epoxy resin based products. For releasing the build up of “tack” from the trowel. For quick instant removal of oil and grease spillages from concrete and painted floors.

EPOXY PRODUCTS CLEANING SOLVENT is the approved cleanser when handling all Epoxy Products Limited epoxy resin based materials.

EPOXY PRODUCTS CLEANING SOLVENT has been developed to provide an immediate and effective cleanser for most hard floor areas

Available in 5 litre tins.

Epoxy Products Limited
Unit 7 Haviland Road
Ferndown Ind. Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983
Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

Cleaning Solvent



Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds

CLEANERS

Epoxy Products Limited
Unit 7 Haviland Road
Ferndown Ind. Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983
Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

DESCRIPTION

EPOXY PRODUCTS CLEANING SOLVENT is a carefully formulated blend of solvents designed for the rapid removal of wet epoxy resin materials from hand tools and mixing equipment. As an excellent cleanser to release the build up of “tack” from the face of the application trowel. To remove oil and grease and others forms of contamination from bare concrete, painted floors, ceramic tiles and most epoxy resin based flooring. It has outstanding cutting strength and will quickly and efficiently restore contaminated floors back to their original pristine condition.

USES: For the general cleaning of all hand tools and mixing equipment when handling epoxy resin based materials. For the cleaning of the trowel face to release the build up of tack during the application of PATCHING MORTAR, EPOXY MORTAR and EPOXY SCREED HD flooring. For the rapid removal of oil and grease patches from concrete, painted floors, ceramic tiles and most Epoxy Resin flooring systems.. Excellent localised patch degreaser prior to subsequent floor painting.

APPLICATION: When cleaning tools and equipment pour a small amount into a small plastic bucket and apply with a small paint brush. When releasing the build up of tack from the trowel apply using a cloth or small paint brush. Always keep the screw cap on the tin and store carefully away from naked flames.

CAUTION: This product is flammable and must be used with extreme caution.

HEALTH AND SAFETY: Always read the Health & Safety Data Sheet prior to handling this product. Avoid skin and eye contact. If eye contact is made then rinse with clean cold water and seek immediate medical advise.

PRODUCT DATA

APPEARANCE / ODOUR

Clear, colourless liquid with mild alcoholic odour

SPECIFIC GRAVITY @ 20°C

0.830 - 0.840

FLASH POINT

This product is highly flammable with a flash point of 12⁰C Min.

STORAGE

Flammable/Combustible. Keep away from heat, flames and direct sunlight.

PERSONAL PRECAUTIONS

Avoid breathing vapours. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Extinguish all ignition sources. Do not smoke when handling this product. Provide good ventilation when handling and confine all spillages. Read Health and Safety Data Sheet prior to handling this product.

PACK SIZE

5 Litre tin