

Epoxy Filler



*Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds*

SPECIALIST PRODUCTS

Epoxy Products Limited
7 Haviland Road
Ferndown Industrial Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983
Email: sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

- ▲ **Twin Pack - Mixed Equal Volumes**
- ▲ **Rapid Strength Development**
- ▲ **Superb Adhesion**
- ▲ **Excellent Chemical Resistance**



EPOXY PRODUCTS EPOXY FILLER is an epoxy resin based filler for concrete crack repair, joint sealing and tile grouting.

EPOXY PRODUCTS EPOXY FILLER is an epoxy resin compound ideal for permanent repairs to cracks found in concrete, stone and brickwork. It is a twin pack material, mixed 50/50 by volume. Only mixing what you need and thus minimising wastage. No primer is required. Ideally suitable for concrete crack repairs found to water retaining structures and potable water structures as it is virtually odourless and non toxic.

An EPOXY PRODUCTS EPOXY FILLER repair is virtually indestructible and its outstanding chemical resistance and adhesion properties are unequalled.

It is available in 1 Litre packs. .



Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds

SPECIALIST PRODUCTS

Epoxy Filler

DESCRIPTION

EPOXY PRODUCTS EPOXY FILLER is a highly sophisticated two part epoxy resin paste that will bond together most building substrates when dry. The adhesive strength and chemical resistance is exceptionally high.

USES: For the permanent repair to concrete joints, cracks found in concrete and stone. Ideally suitable for use in swimming pools and water retaining structures for crack repairs or ceramic tile bedding.

PREPARATION: Surfaces must be dry, free from grease, oil and other forms of contamination. Wire brushing is advisable. Remove any loose materials and brush clean. Cleaning is imperative and the best results can be achieved by use of **EPOXY PRODUCTS CONCRETE CLEANER**.

MIXING: Take equal quantities from Pack A (Resin) and Pack B (Hardener) and mix until a uniform grey is achieved. Mixing is carried out with a flat blade knife. Do not mix more than can be used in approximately 30 minutes. Wash hands thoroughly using soap and water immediately after use. See separate Health & Safety Data Sheet.

APPLICATION: Immediately after mixing press the EPOXY FILLER firmly into the joint or crack or into position behind the tile using a scraper. Hairline cracks should be widened using an angle grinder.

HEALTH AND SAFETY: As some people find Epoxy based products irritant to the skin, all users are recommended to use barrier cream and thoroughly wash with soap and water after use. Avoid skin and eye contact. If eye contact is made then rinse with clean water and seek immediate medical advice.

PRODUCT DATA

COVERAGE

1 Litre will seal 7 linear metres of joint measuring 12mm x 12mm.

POT LIFE

When fully mixed, approximately 30 minutes @ 20⁰ C. Extended pot life at lower temperatures, reduced at higher temperatures.

CURING TIME

Initial cure after 24 hours @ 20⁰ C. Full cure after 7 days.

CHEMICAL RESISTANCE

Resistant to spillages of many chemicals commonly met within industry.
Contact Technical Services for more advice.

TOOL CLEANING

Clean all tools with **CLEANING SOLVENT**.

COLOUR

Pale Grey or White

PACK SIZE

1 Litre set.

Whilst Epoxy Products Limited endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it can not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.

Epoxy Products Limited
7 Haviland Road
Ferndown Industrial Estate
Wimborne
Dorset
BH21 7RZ

Phone: 01202 891899
Fax: 01202 896983
Email:

sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk