

# MATERIAL SAFETY DATA SHEET

## SELF LEVELLING FLOORING AS - PACK A

### 1. Identification of the substance/preparation and company.

Product Name : Epoxy Products Self Levelling Flooring AS - Pack A  
 Product Type : Epoxy Resin  
 Application : Epoxy Resin Floor Topping.  
 Supplier: Emergency Telephone Number: (01202) 891899  
 Epoxy Products Limited, 7 Ferndown Industrial Estate, Wimborne, Dorset. BH21 7RZ England

### 2. Hazards Identification

Main Hazards Irritant  
 Dangerous for the environment.

Human Health Hazards Irritating to eyes and skin. May cause sensitisation by skin contact  
 Safety Hazards Not classified as flammable but will burn  
 Environmental Hazards Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

### 3. Composition/Information on Ingredients

Chemical Nature Mixture of epoxy resin liquids

#### Preparation - Hazardous Ingredients (Europe)

Component	CAS/EINECS	Concentration %	Classification	Risk Phrases
Epoxy Resin Bisphenol Type A (Mol.Wt.<700)	25068-38-6	60-70	Xi, N	R36/38, R43, R51/53
Epoxy Resin Bisphenol Type F (Mol. Wt.<700)	28064-14-4	30-40	Xi, N	R36/38, R43, R51/53
Aliphatic glycidyl ether	68609-97-2	2.50 - 10.00	Xi, N	R38, R43, R51/53

### 4. first-aid Measures

Eye Contact Immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held apart during irrigation to ensure water contact with entire surface of eyes and lids. Seek immediate medical attention.

Skin Contact Wipe off as much as possible with a clean cloth. Wash skin with thoroughly with soap and water. Solvents should not be used to clean the skin because they may increase the penetration of the material.

Ingestion Wash out mouth with water. If accidentally swallowed, give large quantities of water or milk or dilute the effects on the stomach. Do not. Induce vomiting. Seek immediate medical attention.

Inhalation Remove from exposure to fresh air. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.

### 5. Fire-fighting Measures

Extinguishing Media Use foam, water spray or carbon dioxide.  
 Extinguishing Media – Not suitable Do not use water jet.  
 Special Hazards of Product Combustion will produce smoke, carbon dioxide and carbon monoxide.  
 Protective Equipment for Fire-Fighting Wear full protective clothing and self-contained breathing apparatus.

### 6. Accidental Release Measures

Personal Precautions Avoid contact with skin, eyes and clothing  
 Environmental Precautions and Clean-up methods Try to prevent the material from entering the drains or water courses.  
 Spillages Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal

### 7. Handling and Storage

Handling Avoid contact with eyes, skin and clothing  
 Storage Store in the original container securely closed.  
 Storage temperature Ambient

### 8. Exposure Controls/Personal Protection

Engineering Control Measures Use of the basic principles of Industrial Hygiene will enable this material to be used safely.  
 Respiratory Protection Not normally required. In confined areas a half mask respirator with organic vapour cartridge and particulate filter NPF 20 (gas only)  
 Hand Protection Butyl or nitrile type gloves or any impermeable gloves must be worn. The inside of the gloves must be kept clean  
 Eye Protection Safety eye glasses must be worn.  
 Skin and Body Protection Standard issue work clothes.

### 9. Physical and Chemical Properties

Physical State Liquid  
 Colour Various  
 Odour Slight  
 Ph ca. 7  
 Boiling Point >200° C  
 Flash Point >150° C  
 Auto Ignition Temperature >300° C  
 Vapour Pressure < 0,01 Pa at 20° C  
 Water Solubility Negligible  
 Density 1.80g/cm<sup>3</sup> at 20° C  
 Viscosity Not applicable

### 10. Stability and Reactivity

Conditions to avoid  
 Materials to avoid  
 Hazardous Decomposition Products  
 Hazardous Reactions

Caustic soda can induce vigorous polymerisation at temperatures around 200°C.  
 Strong oxidising agents. Caustic soda.  
 Hazardous decomposition products are not expected to form during normal storage.  
 Stable under normal use conditions. Reacts with strong oxidising agents.  
 Polymerises exothermically with amines, mercaptans at ambient temperatures.  
 Polymerises in contact with caustic soda. Reacts exothermically with bases (eg. caustic soda), ammonia, primary and secondary amines, alcohols and acids.

**11. Toxicological Information**

Acute Oral Toxicity  
 Acute Dermal Toxicity  
 Eye Irritation  
 Skin Irritation  
 Sensitisation  
 Carcinogenicity  
 Mutagenicity

Expected to be of low toxicity. LD50 > 2000 mg/kg  
 Expected to be of low toxicity. LD50 > 2000 mg/kg  
 Expected to be slightly irritant.  
 Expected to be slightly irritant.  
 Expected to be a skin sensitiser.  
 Not expected to be carcinogenic.  
 Not considered to be a mutagenic hazard.

**12. Ecological Information**

Persistence/Degradability

Biodegradable  
 Bioaccumulation  
Ecotoxicity Effects  
 Toxicity to fish  
 Toxicity to algae  
 Acute toxicity to invertebrates  
 Mobility  
 Sewage treatment  
 Basis for assessment

This product is expected to be not readily biodegradable.  
 Has the potential to bioaccumulate.  
 Expected to be very toxic. LC/EC/IC 50 > 1 mg/l  
 Expected to be toxic 1. LC/EC/IC 50 > 10 mg/l  
 Expected to be toxic 1. LC/EC/IC 50 > 10 mg/l  
 The product is insoluble in water and sinks in water.  
 Expected to be practically non toxic 1. LC/EC/IC 50 > 100 mg/l  
 Information given is based on knowledge of all the components and the toxicology of similar products

**13. Disposal**

Product Disposal  
 Container Disposal  
 Local legislation

Recover and recycle if possible. Arrange for disposal via a licensed waste contractor.  
 Dispose of containers with care. Empty packaging should be removed by a licensed waste contractor.  
 The recommendations given are considered appropriate for safe disposal. However, local regulations maybe more stringent and these must be complied with.

**14. Transport Information**

**ADR / RID**

UN Number  
 Class  
 Classification Code  
 Packaging Group  
 Labelling Number  
 Risk Number  
 Description of the goods contains

3082  
 9  
 M6  
 111  
 9  
 90  
 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. EPOXY RESIN

**ICAO / IATA-DGR**

UN Number  
 Class  
 Packaging Group  
 Proper Shipping Name

3082  
 9  
 111  
 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. EPOXY RESIN

**IMDG**

UN Number  
 Class  
 Packaging Group  
 Labelling Number  
 Description of the goods contains

3082  
 9  
 111  
 9  
 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. EPOXY RESIN

**15. Regulatory Information**

Labelling according to EC Directives  
 Classification

EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT < 700)  
 Irritant  
 Dangerous for the environment

Symbol (s)



X - IRRITANT



N - DANGEROUS FOR THE ENVIRONMENT

Risk Phrases - R

R36/38  
 R43  
 R51/53

Irritating to eyes and skin  
 May cause sensitisation by skin contact.  
 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

Safety Phrases - S

S24  
 S26  
 S28A  
 S37/39

Avoid contact with skin  
 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 After contact with skin, wash immediately with plenty of water.  
 Wear suitable gloves and eye/face protection.

S46	If swallowed seek medical advice immediately and show this container or label.
S61	Avoid release to the environment. Refer to special instructions/safety data sheet.

**Notification Status**

TSCA	All components listed
AICS	All components listed
DSL	All components listed
IECSC	All components listed
EINECS	All components listed or polymer exempt
KECI (KR)	All components listed
PICCS (PH)	All components listed

**16. Other Information**

Date Issued	01.04.2008
Reference	SLFASA/03
Product Code	Epoxy Products Self Levelling Flooring (Resin - Pack A)
Intended Use	Epoxy Resin floor Topping.

The information is based on our current knowledge and is intended to describe the product for the purpose of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

# MATERIAL SAFETY DATA SHEET

## SELF LEVELLING FLOORING AS PACK B

### 1. Identification of the substance/preparation and company.

Product Name : Self Levelling Flooring AS (Hardener - Pack B)  
Product Type : Epoxy Resin Curing Agent  
Application : Epoxy Resin Floor Topping  
Supplier: Emergency Telephone Number: (01202) 891899  
Epoxy Products Limited, 7 Ferndown Industrial Estate, Wimborne, Dorset. BH21 7RZ England

### 2. Hazards Identification

Harmful by Inhalation and if swallowed (R20/22). May cause sensitisation by skin contact (R43).

### 3. Composition/Information on Ingredients

#### 3.1. Composition/Information on Ingredients

CAS Number and Chemical Name	%	Classification
100-51-6 Benzyl Alcohol	> 45	Xn; R20/22
Description	: Cycloaliphatic Amine	

### 4. first-aid Measures

INGESTION : If swallowed seek medical advice immediately. Induce vomiting or remove stomach contents by gastric suction only as directed by Medical personnel.

INHALATION : Move patient to fresh air. If breathing has stopped or is laboured give assisted respiration (e.g. mouth to mouth). Supplemented oxygen may be indicated. Seek medical advice. Assure mucus does not obstruct airway. Prevent aspiration of vomit. Turn victim's head to one side.

SKIN CONTACT : Remove product and immediately flush affected area with water for at least 15 minutes.

EYE CONTACT : Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Seek medical advice immediately.

### 5. Fire-fighting Measures

#### Suitable Extinguishing Media

Ignition will give rise to a Class B fire. In case of fire use: Water Spray, Carbon Dioxide (Co<sup>2</sup>), Dry Chemical Alcohol Foam.

### 6. Accidental Release Measures

Prevent accidental spillages to enter streams or drinking water supplies.

### 7. Handling and Storage

Handling : Avoid contact with eyes. Avoid breathing vapours.

Storage : Keep away from acids, Epoxy Resins, heat and oxidizers. Protect containers from physical damage.

### 8. Exposure Controls/Personal Protection

100-51-6 TWA Values : Not established

#### 8.2. Personal Protection

a) Respiratory Protection : Not required.

b) Hand Protection : Nitrile rubber gloves or any impermeable gloves must be worn.

c) Eye Protection : Safety Eye Glasses

d) Skin Protection : Protective long sleeved overalls must be worn.

### 9. Physical and Chemical Properties

Appearance : Mobile liquid

Odour : Ammoniacal

pH : Alkaline

Boiling Point : 222C (432F)

Flash Point : 103C (219F) (Closed Cup Method)

Flammability : Not applicable

Auto-ignition Temperature : No data

Explosive Limits : No data

Vapour Pressure : 13 @ 54C (130F)

Relative Density : 1.15

Water Solubility : Slightly

Partition Coefficient : n-Octanol/Water: not applicable

Viscosity : no data

### 10. Stability and Reactivity

Oxidizing Agents (i.e. perchlorates, nitrates etc.). A reaction accompanied by large heat release occurs when the product is mixed with acids or Epoxy Resins. Heat generated may be sufficient to cause a hazard due to splashing of hot material.

#### HAZARDOUS DECOMPOSITION PRODUCTS

Ammonia when heated. Carbon Monoxide in a fire. Carbon Dioxide in a fire. Nitrogen Oxides in a fire. Hydrogen Cyanide when heated. Combustion of product under oxygen-starved conditions can be expected to produce numerous toxic products including: nitriles, cyanic acid, isocyanates, amides and carbamates.

#### HAZARDOUS POLYMERISATION

Will not occur.

### 11. Toxicological Information

Oral LD50 (rat) : 620 mg/kg (estimate) Data available on components only.

Dermal LD50 (rabbit) : > 1000 mg/kg (estimate) Data available on components only.

Inhalation LC50 (rat) : No Data (Estimate) Data available on components only.

## **12. Ecological Information**

Waste from this product may present long term environmental hazards, thus landfill must be considered less acceptable than incineration.

## **13. Disposal Considerations**

Dispose of in accordance with local and national regulations. For example, in the UK regulations made under the Control of Pollution Act 1974 and the Environmental Protection Act 1990. Wear protective clothing during disposal operations. If disposal is by a waste contractor, make sure that he has sufficient information and that waste containers are properly labelled.

## **14. Transport Information**

ADR/RID SHIPPING DATA : Not regulated  
IMO SHIPPING DATA : Not regulated  
ICAO/IATA SHIPPING DATA : Not regulated  
IS THE PRODUCT CLASSIFIED AS A MARINE POLLUTANT? No

## **15. Regulatory Information**



### **HARMFUL/IRRITANT**

EEC SYMBOL Harmful/Irritant (Xn)

EEC Council Directive relating to the classification, packaging and labelling of dangerous substances and preparations Risk ® and Safety (S) phrases Harmful by inhalation and if swallowed (R20/220. May cause sensitization by skin contact (R43).

In case of contact with eyes, rinse thoroughly with plenty of water and seek medical advice (S26). Wear suitable gloves and eye/face protection (S37/39).

## **16. Other Information**

Date Issued : 12.04.2008  
Reference : SLFAS/03  
Intended Use : Epoxy Curing Agent  
Product Code : Epoxy Self Levelling Flooring AS (Pack B - Hardener)

The information is based on our current knowledge and is intended to describe the product for the purpose of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.