



Manufacturers of High
Performance Floor
Coatings and

EXTERNAL

Epoxy Products Limited
Unit 7 Haviland Road
Ferndow Dorset
BH21 7RZ
Phone: 01202 891899
Fax: 01202 896983
Email:
sales@epoxyproducts.co.uk
Web:
www.epoxyproducts.co.uk

Epoxy Pointing Mortar

- ▲ Superior to Sand/Cement and Polymeric Sands
- ▲ Good Light Stability and Chemical Resistance
- ▲ Equal Part Mix – Resin Pack + Hardener Pack
- ▲ Range of Natural Colours



EPOXY POINTING MORTAR

We have sourced a natural high purity crystalline quartz grain and treated each individual grain with high quality coloured epoxy resin. Using natural coloured pigments and high quality epoxy resin has provided good light stability and excellent resistance to weather and chemicals.

This twin pack epoxy resin based product offers far superior performances to conventional sand cement mixes and polymeric pointing sands.

Can be applied in wet conditions—even during the rain!

Available in a range of colours.



Manufacturers of High
Performance Floor
Coatings and
Re-Surfacing Screeds

EXTERNAL

Epoxy Products Limited
Unit 7 Haviland Road
Ferndow Dorset
BH21 7RZ
Phone: 01202 891899
Fax: 01202 896983
Email:

sales@epoxyproducts.co.uk
Web: www.epoxyproducts.co.uk

Epoxy Pointing Mortar

DESCRIPTION

EPOXY POINTING MORTAR is a far superior performance product to conventional sand/cement mixes and polymeric pointing sands available today. Pave Point is a twin pack epoxy resin product, specifically designed for infilling and grouting between concrete and natural stone slabs. This product can be applied during wet conditions and will not stain the natural stone!

USES: As a lasting grout infill for concrete and stone slabs, block paving and bricks when improved performance is required compared to conventional sand.

PREPARATION: Standard conventional method for bedding and grouting slabs and block paving. Surfaces can be both wet or dry.

MIXING: Take equal part measures from both PACK A (Resin) and PACK B (Hardener) and stir thoroughly together until uniform in colour. For small amounts (avoiding wastage) use a trowel and a plastic mixing bucket. For mixing larger amounts use an electric drill and paddle attachment and a mixing bucket. For pointing work simply add water. If too much water is added, simply pour off the excess water and its ready to use!

APPLICATION: Using the standard conventional method for the permanent placement and bedding of concrete or stone slabs and block paving. This twin pack product can be applied in both dry and wet conditions. You can even apply it in the rain. Brush the EPOXY POINTING MORTAR into the joints and sweep off the excess. It will not stain the slabbing or block paving. Pointing is carried out in the normal way.

HEALTH AND SAFETY:

This product has been classified as being non hazardous.

PRODUCT DATA

COVERAGE

25 kg will cover approximately 10m² of concrete slab joints.

YIELD

25 kgs - 12 litres

COLOURS

Brick Red, Nutmeg, Charcoal and Sandstone

WEATHER RESISTANCE

Resistance to all extreme weather conditions.

LIGHT RESISTANCE

Good UV light resistance.

CHEMICAL RESISTANCE

Resistant to spillages to a wide range of chemicals including oil, grease and petrol.

STRENGTH

The quartz base is extremely hard having a Mohs hardness of 7

PACK SIZE

25 Kg Polythene Bags

Whilst Epoxy Products Limited endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it can not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.